


**IMPERIAL UNITS**
**UNITÉS IMPÉRIALES**

DIA. (NOM.)	O.D.	I.D.	T1	T2	T3	A	B	C	WEIGHT / POIDS		
	D.E.	D.I.							T1	T2	T3
1 1/2	5	2	5/8	3/4	3/4	3 7/8	4	5/8	3.0	3.6	3.6
2	6	2 1/2	5/8	3/4	3/4	4 3/4	4	3/4	3.9	4.7	4.7
2 1/2	7	3	5/8	3/4	3/4	5 1/2	4	3/4	5.2	6.2	6.2
3	7 1/2	3 5/8	5/8	3/4	3/4	6	4	3/4	5.9	7.1	7.1
4	9	4 5/8	5/8	3/4	3/4	7 1/2	8	3/4	7.9	9.5	9.5
5	10	5 5/8	5/8	3/4	3/4	8 1/2	8	7/8	8.9	10.7	10.7
6	11	6 5/8	5/8	3/4	3/4	9 1/2	8	7/8	10.3	12.3	12.3
8	13 1/2	8 5/8	5/8	3/4	7/8	11 3/4	8	7/8	14.7	17.7	20.6
10	16	10 3/4	3/4	1	1	14 1/4	12	1	18.9	30.2	30.2
12	19	12 3/4	3/4	1	1 1/4	17	12	1	32.7	43.5	54.4
14	21	14 3/4	3/4	1 1/8	1 1/4	18 3/4	12	1 1/8	36.6	55.0	78.6
16	23 1/2	16 3/4	3/4	1 1/8	1 1/2	21 1/4	16	1 1/8	44.0	66.0	88.3
18	25	18 3/4	1	1 1/4	1 1/2	22 3/4	16	1 1/4	48.8	81.4	97.6
20	27	20 7/8	1	1 1/4	1 5/8	25	20	1 1/4	69.0	86.3	112.0
24	32	24 7/8	1	1 3/8	2	29 1/2	20	1 3/8	88.0	121.0	176.0
30	39	31	1	1 1/2	2 3/8	36	28	1 3/8	117.0	176.0	279.0
36	46	37	1	1 1/2	2 7/8	42 3/4	32	1 5/8	158.0	237.0	454.0

**SI UNITS**
**UNITÉS SI**

DIA. (NOM.)	O.D.	I.D.	T1	T2	T3	A	B	C	WEIGHT / POIDS		
	D.E.	D.I.							T1	T2	T3
38	127	51	15.9	19.0	19.0	98	4	15.9	1.4	1.6	1.6
50	152	63	15.9	19.0	19.0	121	4	19.0	1.8	2.1	2.1
64	178	76	15.9	19.0	19.0	140	4	19.0	2.4	2.8	2.8
76	191	92	15.9	19.0	19.0	152	4	19.0	2.7	3.2	3.2
102	229	117	15.9	19.0	19.0	190	8	19.0	3.6	4.3	4.3
127	254	143	15.9	19.0	19.0	216	8	22.2	4.0	4.9	4.9
152	279	168	15.9	19.0	19.0	241	8	22.2	4.7	5.6	5.6
203	343	219	15.9	19.0	22.2	298	8	22.2	6.7	8.0	9.4
254	407	273	19.0	25.4	25.4	362	12	25.4	8.6	13.7	13.7
305	483	324	19.0	25.4	31.7	432	12	25.4	14.8	19.7	24.7
356	534	375	19.0	28.6	31.7	476	12	28.6	16.6	25.0	35.7
406	597	425	19.0	28.6	38.1	540	16	28.6	20.0	29.9	40.1
457	635	476	25.4	31.7	38.1	578	16	31.7	22.1	36.9	44.4
508	699	530	25.4	31.7	41.2	635	20	31.7	31.3	39.1	50.9
610	813	632	25.4	34.9	51.0	749	20	34.9	39.9	44.9	80.2
762	985	787	25.4	38.1	60.3	914	28	34.9	53.1	79.8	126.7
914	1169	940	25.4	38.1	73.0	1086	32	41.3	71.7	107.5	206.5

**NOTES**

- Material: T1, T2 mild steel, T3 A516 Gr. 70
- Drilling: ASME B16.5 CL. 150
- For maximum working pressure see technical section.
- Finish: Galvanized
- T1 available on request only

- Matériau: T1, T2 acier doux, T3 A516 Gr. 70
- Perçage: ASME B16.5 CL. 150
- Pour pression maximale voir section technique.
- Fini: Galvanisé
- Épaisseur T1 sur demande seulement.