



3" - 12" USE I.D. SLIP-ON
14" - 36" USE I.D. REGULAR
3" - 12" SLIP-ON - SEE TABLE BELOW
14" - 36" SLIP-ON - USE I.D. REGULAR

3" - 12" UTILISER D.I. COULISSANTES
14" - 36" UTILISER D.I. RÉGULIÈRES
3" - 12" COULISSANTES - VOIR TABLEAU PLUS BAS
14" - 36" COULISSANTES - UTILISER D.I. RÉGULIÈRES

DIA. (NOM.)	IN / PO	3	4	5	6	8	10	12
	mm	75	100	125	150	200	250	300
OUTSIDE DIA. DIA. EXTÉRIEUR	IN / PO	7½	9	10	11	13½	16	19
	mm	190	229	254	279	343	407	483
INSIDE DIA. DIA. INTÉRIEUR	IN / PO	4 1/8	5 1/8	6 1/8	7¼	9¼	11 3/8	13 3/8
	mm	105	130	156	184	235	289	340
T1	IN / PO	5/8	5/8	5/8	5/8	5/8	5/8	3/4
	mm	15.9	15.9	15.9	15.9	15.9	15.9	19
T2	IN / PO	3/4	3/4	3/4	3/4	3/4	1	1
	mm	19	19	19	19	19	25.4	25.4
T3	IN / PO	3/4	3/4	3/4	3/4	7/8	1	1¼
	mm	19	19	19	19	22.2	25.4	31.7
NUMBER OF BOLTS NOMBRE DE BOULONS			4	8	8	8	12	12
BOLT CIRCLE DIA. C. DES BOULONS	IN / PO	6	7½	8½	9½	11¼	14¼	17
	mm	152	190	216	241	298	362	432
DIA. OF HOLES DIA. DES TROUS	IN / PO	3/4	3/4	7/8	7/8	7/8	1	1
	mm	19	19	22.2	22.2	22.2	25.4	25.4
WEIGHT (T1) POIDS (T1)	LB	5.2	6.6	7.5	8.8	12.6	16.4	29.2
	kg	2.4	3.0	3.4	4	5.7	7.4	13.2
WEIGHT (T2) POIDS (T2)	LB	6	8.2	8.5	10.4	15.2	26.2	39
	kg	2.7	3.7	3.9	4.7	6.9	11.9	17.7
WEIGHT (T3) POIDS (T3)	LB	6	8.2	8.5	10.4	20.0	26.2	48.4
	kg	2.7	3.7	3.9	4.7	9.1	11.9	22.0

NOTES

- Material: T2, mild steel.
T1, T3, A516 Gr. 70. upon request
- Drilling: ASME B16.5 CL. 150

- Matériau: T2, acier doux.
T1, T3, A516 Gr.70. sur demande seulement
- Perçage: ASME B16.5 CL. 150.